

EZ-202 Wire Rope & Chain Lubricant

Heavy Duty High-performance Grease



EZ-202 wire rope & chain lubricant is clay based grease made from a high viscosity petroleum base oil with a high viscosity index (VI). Synthetics and EZ special additives simplify application and improve penetration and wetting. Chemical extreme pressure (EP) additives and lubricating solids including moly disulphide enhance film strength, corrosion protection & water repelling properties.

Features & Benefits

- ▶ Sprayable for Automatic dispensing
- ▶ Excellent penetration of Rope strands
- ▶ Tough outer film protects ropes, sheaves & chain links
- ▶ Anti wear formulation
- ▶ Tough outer film resists chipping & peeling at low ambient temperatures

Tips for better performance

- ▶ Ideal choice for steel, cement, mining, paper, textile & chemical industry for increased regreasing frequency

Applications

- ▶ Wire ropes & chain in general and severe service
- ▶ Recommended for mining, construction, marine, steel, cement and forest industries

Operating Temperature Range

- ▶ **EZ-202 wire rope & chain lubricant** is recommended for use over temperature range -25°C to 160°C



EZ-202 Wire Rope & Chain Lubricant

Heavy Duty High-performance Grease

Typical Properties: EZ-202 Wire Rope & Chain Lubricant

| Attributes | Ref. Method | Specifications |
|---------------------------------|---------------|-----------------|
| Appearance | Visual | Black-Tacky |
| Flash point °C | | 195 °C+ |
| Base oil viscosity 1. @40 °C | ASTM D 445 | >270 1000 |
| Viscosity Index (base fluid) | | 100 |
| Four ball - weld | IP 239 | 800 kg |
| Scar mm | ASTM D 2296 | 0.4 mm |
| Health: 0 | Reactivity: 1 | Flammability: 1 |

Available in 18 kg pack, 180 kg drums & 240 gm aerosol pack

Other World Leading Products from ITW Chemin

Automotive Solutions

MET-L-HOLD
Precision Chucks and Solutions
Workholding Devices

MET-L-COOL
Cut Machining Costs. Power Profits.
Metal Working Fluids

MET-L-GARD
Eliminate Rust. Improve Profits.
Rust Preventive Chemicals

MET-L-KLEEN
Aqueous Cleaners

Accu-Lube®
Microlubrication Systems

PLEXUS®
Structural Adhesives

Maintenance, Repair, Overhaul Solutions

LPS
Lubricants, Cleaners,
Degreasers

Devcon®
Metal-filled Epoxies
and Urethanes

RUSTLICK 631
Loosens • Lubricates • Maintains
Instant Rust Fighter
in Aerosol Can

**EC
Clean**
Contact Cleaner

ITW DYKEM
Marking System, Staining Colours
and Steel Blue Layout Liquids

Automotive After Market Solutions

Wynn's
Complete Automotive Maintenance

ITW Chemin
A business unit of ITW Inc. USA
Specialty Chemicals, Lubricants and Equipment Manufacturers



 ISO 9001
 ISO 14001
 OHSAS 18001

ITW India Limited, Plot No. 34 to 37, Phase-2, IDA, APIIC Pashamylaram, Medak Dist. - 502 307(35 km from Hyderabad), A.P. India.
Telephone: +91-8455-224700, 01, 03, 04, 06, 07, 08. Facsimile: +91-8455-224705. Website: www.itwchemin.com

Material Safety Data Sheets available on www.itwchemin.com