

EZ 602 HS2 PLUS

Heavy duty High-performance Grease

EZ 602 HS2 is multi purpose high performance Grease consisting of lithium complex based thickener and Mineral lubricating oils. It is formulated to provide a heavier oil film for applications with excessive loading at slow speeds and high temp.. It's superiority in water resistance, oxidation stability, corrosion protection and high dropping point makes it a unique choice for rugged application requirements



Features & Benefits:

- Excellent wear protection & Good Rust preventive properties
- Metal passivators for protection of alloy steel
- Higher base oil viscosity , ISO VG 460 , to increase load carrying capacity
- Resistance to hot & cold water and good shear stability
- oxidation stability extends life even at elevated temperatures

Tips for better performance:

- Maintaining a clean work environment while greasing the equipment
- Clean the grease fittings prior to grease injection
- Periodic lubrication with fresh grease as per the schedules

Typical Applications:

- Ideal choice for steel, cement, mining, paper & chemical industry.
- Heavy duty, slow moving plain and rolling element bearings operating in the severe environments under following conditions:
 - Heavy / shock loads
 - High temp.
 - Water rich environments
 - High level of vibrations

Parameters:

Attributes	Ref. Method	Specification (EZ 602 HS2)
Appearance	Visual	Smooth and tacky
Colour	Internal	Amber to brown thick color
NLGI Grade	Grade – 2	Grade - 2
Thickener Type		Lithium Complex
Penetration	ASTM D 217	265-295
Dropping Point °C	ASTM D 2265	> 260
Base oil viscosity	ASTM D 445	
1. @ 40 °C		100 cSt
2. @ 100 °C		14 cSt
Viscosity Index	Internal	NA
Four Ball – Weld	IP 239	600 Kg
- LWI	ASTM D 2596	-
- Scar mm	ASTM D 2296	-
Water spray off	ASTM D 1264	Less than 3.0%
Oil Separation %	ASTM D 1742	0
Copper corrosion	ASTM D 90	1B
Rust prevention	ASTM D 1743	Pass

Technical data details should be considered representative or typical values only and should not be used for specification purposes.

Note*: Changes in the appearance of the product have no detrimental effect on the Quality /Performance of the product.

Packaging Details: EZ602 HS2 in 180KG and 20KG

Storage & Safety: This product is unlikely to present any significant health or safety hazard when used as recommended. Good standards of personal and industrial hygiene are to be maintained by the user - (Refer Safety Data Sheet).

Disclaimer: Information contained in this data sheet is based upon the properties and applications of use known to us. However, generally no legal liability may be deducted from such information.



ITW India Private Limited, Plot No. 34 to 37, Phase-2, IDA, TSIC, Pashamylaram, Sangareddy Dist. -502 307, Telangana State., India.

Telephone: +91 - 8455 - 224700, 01, 03, 04, 06, 07, 08. Facsimile: +91 - 8455 - 224705. Website: www.itwchemin.com

Regd. Office: ITW India Private Limited, Level 1, Lotus Plaza, 732/1, Mehrauli Gurgaon Road, Sector-14, Gurgaon - 122 001, Haryana, India.

Telephone : +91 - 124 - 4284381, Facsimile : +91 - 124 - 4284389, E-mail : infoindia@itw.com

Corporate Identity Number (CIN) : U32301HR1979PTC038643

Speciality Chemicals & Lubricants Manufacturers