

# Rust-O-Wax **Blue**

## Blue Waxy Anti-Corrosion Spray

### Technical Data Sheet

**Rust-O-Wax Blue** is a long term outdoor and indoor corrosion protection from rust and corrosion for machined surfaces and assemblies subjected to long periods of storage or adverse shipping conditions. The bluish, waxy non-brittle film is highly resistant to humidity and severe corrosive atmospheres.



#### AREAS OF APPLICATION:

- Finished metallic components
- In-process metal spares parts
- Bare metal surfaces & Parts
- Metallic dies & molds
- Farm Machinery
- Harbor industry
- Transportation industry, Servicing/Repairing and maintenance.
- Effective corrosion shield for overseas shipments, winterizing of farm machinery outdoor storage.
- To be used for brine and chloride resistance in refrigeration plants.
- In paper and pulp plants.
- As a cable end sealer and pipe joint protector in utilities.
- Protection of air conditioning and electrical equipment in hospitals and Educational institutions

## ADVANTAGES AND BENEFITS:

- Fast Drying
- Can be removed easily
- Waterproof and resistant to weathering
- Good corrosion and oxidation protection
- Highly effective due to good film-forming properties
- Suitable for all climate zones

## TYPICAL PARAMETERS:

Parameter	Reference Method	Rust-O-Wax Blue
Appearance	Visual	Blue
Density- Bulk	ASTM D 1298	0.80±0.02 gm/ml
Optimum Film Thickness	IS 1154	40-45µ
Film Type	Visual	Waxy, Dry
Drying time		15 minutes
Surface covering	IS 1154	8-9 m <sup>2</sup> /can
Salt Spray Resistance @ 50µ	ASTM B 117	1000 hrs Minimum

- Technical data details should be considered representative or typical values only and should not be used for specification purposes.

**PACK SIZE:** 400ml Aerosol.

**Storage & Safety:** This product is unlikely to present any significant health or safety hazard when used as recommended. Good standards of personal and industrial hygiene are to be maintained by the user - (Refer Safety Data Sheet).

**Disclaimer:** Information contained in this data sheet is based upon the properties and applications of use known to us. However, generally no legal liability may be deducted from such information.



ITW India Private Limited, Plot No. 34 to 37, Phase-2, IDA, TSIC, Pashamylaram, Sangareddy Dist. -502 307, Telangana State., India.

Telephone: +91 - 8455 - 224700, 01, 03, 04, 06, 07, 08. Facsimile: +91 - 8455 - 224705. Website: [www.itwchemin.com](http://www.itwchemin.com)

Regd. Office: ITW India Private Limited, Level 1, Lotus Plaza, 732/1, Mehrauli Gurgaon Road, Sector-14, Gurgaon - 122 001, Haryana, India.

Telephone : +91 - 124 - 4284381, Facsimile : +91 - 124 - 4284389, E-mail : [infoindia@itw.com](mailto:infoindia@itw.com)

Corporate Identity Number (CIN) : U32301HR1979PTC038643

Speciality Chemicals & Lubricants Manufacturers

Revised on: July'18/04