

# EC CLEAN

## Electric and Electronic Equipment Instantly Cleaner

EC Clean is an excellent rapid acting solvent specifically formulated for easier maintenance of electrical and electronic components and equipment. It enhances efficiency and ensures excellent cleaning.



### Application Areas:

Electrical equipment such as PCB, commentators, motors, coils, contacts, relays, PBX equipment, telephone CT boxes, office equipment, magnetic tape heads, TV tuners, computer keyboards, switches, connections, circuit-breakers, electro-mechanical assemblies, fuses, fuse gauges, switch gears, testers, solenoids, terminal blocks, ignition filters, battery terminals, bus bars, gauges and delicate mechanisms.

### Excellent Penetration

EC Clean, because of its low surface tension has a very good penetrating property thereby flushing out dirt, oil, flux and grease from even the most intricate parts.

### Quick Drying

EC Clean has a rapid drying action thereby ensuring no attraction of dust, foreign particles immediately after cleaning which would otherwise lead to tracking of the circuits.

### Rapid Cleaning

EC Clean has a very rapid cleaning action which reduces maintenance downtime.

### Non-Corrosive

EC Clean has a high purity formula for high reliability and is non-corrosive on most paints, rubber, plastics, varnishes and lacquers.

### Non-Staining

EC Clean leaves surfaces clean and dry, with no oily and powdery residues.

EC Clean is an environment friendly product containing no CTCs or CFCs. EC Clean is a non-carcinogenic, non-chlorinated solvent which is very safe to use. It does not induce any moisture into the windings.

### Directions for Use

- Apply liberally by spraying and allow the liquid to run off. Use extension tube for pinpoint cleaning.
- Use on surfaces with heavy carbon deposit.
- Remove residue with intermittent spray.
- Allow to thoroughly dry and vent before re-activating the system.
- Periodic application of EC Clean prolongs life expectancy of components and helps eliminate the formation of oxidation and carbon deposits that cause leakage.

### Properties:

Sp. Gravity	-	0.7
Drying time	-	<1(ethyl ether=1)
Surface tension	-	20 mN/cm
Flash point	-	-4°C
VOC Content	-	100%
Percentage CFC	-	0%

Pack Size: Available in 350 ml & 400 ml pack.

Note: Please Refer Safety Data Sheet before Use.



**ITW India Private Limited, Plot No. 34 to 37, Phase-2, IDA, TSIC, Pashamylaram, Sangareddy Dist. -502 307, Telangana State., India.**  
Telephone: +91 9000031515, 9100012393. Website: [www.itwchemin.com](http://www.itwchemin.com)

Regd. Office: ITW India Private Limited, Level 1, Lotus Plaza, 732/1, Mehrauli Gurgaon Road, Sector-14, Gurgaon - 122 001, Haryana, India.  
Telephono : +91 124 - 4284381, Facsimile : +91 - 124 - 4284380, E mail : [infoindia@itw.com](mailto:infoindia@itw.com)

Corporate Identity Number (CIN) : U32301HR1979PTC038643, GSTIN : 36AAAC14550Q127

Speciality Chemicals & Lubricants Manufacturers