

# RUSTLICK 631

## Technical Data Sheet

---

**RUSTLICK 631** is a new-age solution to an age-old problem. It fights rust ensuring your equipment and components stay perfect and function smoothly. It is a solution that works in Minutes, negating costly Maintenance downtime, is for you - the world-renowned rust-buster. Widely recognized for crafting value-added products and innovative customer solutions



### Features:

- Loosens rusted parts
- Cleans & Protects
- Lubricates and Maintains Long-term rust prevention Moisture Repellent
- High dielectric strength – Good insulator
- Precision tolerance unaffected due to thin film
- Restores the electrical properties and enhances the life of the part Convenient to use even for intricate parts
- Easy, non-messy application

### Typical Applications:

- Conventional mechanical maintenance Electrical maintenance
- Industrial and Automotive Applications Household applications
- Component protection

## **Propellant:**

- LPG in 370 & 133 ml
- CO2 in 400 ml

## **Typical Properties:**

Attributes	Test Method	Specification
Appearance	Visual	Clear Amber/Brown liquid
Odor	Olfactory	Pleasant Odor
Specific Gravity @27°C	ASTM D 1298	0.770-0.840
Kinematic Viscosity @ 37.8°C	ASTM D 445	2.0 - 3.0 cSt
Flash Point	ASTM D 93	>60°C
Film Thickness	IS 1154	2.0 – 3.0 microns
Water Displacement Test	IS 1154	Passes
Salt Spray Protection	ASTM B 117	Minimum 48 Hours

- Technical data details should be considered representative or typical values only and should not be used for specification purposes.

## **Directions to Use:**

- Shake well prior to use
- Hold the Rustlick 631 aerosol can 4 – 6 inches away and spray the area to be cleaned and lubricated
- Use extension tube for pin point application Allow sufficient time for rust smash to act
- Safe on plastic, rubber, metal and painted surface

**Safety Information:** This product is unlikely to present any significant health or safety hazard when used as recommended. Good standards of personal and industrial hygiene are to be maintained by the user - (Refer Safety Data Sheet before use).

**Disclaimer:** Information contained in this data sheet is based upon the properties and applications of use known to us. However, generally no legal liability may be deducted from such information.



**ITW India Private Limited, Plot No. 34 to 37, Phase-2, IDA, TSIC, Pashamylaram, Sangareddy Dist. -502 307, Telangana State., India.**  
Telephone : +91 9000031515, 9100012393. Website: [www.itwchemin.com](http://www.itwchemin.com)

Regd. Office: ITW India Private Limited, Level 1, Lotus Plaza, 732/1, Mehrauli Gurgaon Road, Sector-14, Gurgaon - 122 001, Haryana, India.  
Telephone : +91 124 - 4284381, Facsimile : +91 - 124 - 4284380, E mail : [infoindia@itw.com](mailto:infoindia@itw.com)

Corporate Identity Number (CIN) : U32301HR1979PTC038643, GSTIN : 36AAAC14550Q127

Rev on: Nov 22/ Ver# 09

Speciality Chemicals & Lubricants Manufacturers