

# ZINC BULK

**Zinc Bulk** is a galvanizing coating specially designed to meet the requirements of hot dip galvanized parts. The coating protects metal surfaces against rust and corrosion giving a flexible coat.







### **FEATURES:**

- Rust protection coating on welded and drilled surfaces.
- Conforms to ASTM A780 & MIL- P- 21035 (galvanic repair)
- Acts as an antirust primer
- Touch up galvanized surfaces.
- · Offers excellent mechanical toughness
- Coating resistant to salt water and temperatures up to 350
- Nontoxic
- No ozone depleting solvents
- Dries to touch in 10 15 min

## **APPLICATIONS:**

- Structural steel
- Damaged Galvanized surfaces
- Auto and truck bodies
- Marine installations
- Repair of storage tanks
- Fences
- Welds
- Towers
- Exhaust Stack
- Outdoor furniture and tools
- Heating and air conditioning equipment

### **PROPERTIES:**

Appearance : Dark Grey metallic appearance

Resin Type : Organic Resin

Pigment Type : Zinc dust (>92% on dry film as per ASTM A780)

Coverage per Unit : 35 Sqmt \10Kgs @ 4 mils

Specific Gravity : 2.9±0.2 Flash Point (solvents) : 25 °C

#### **APPLICATION CONDITIONS:**

Minimum ambient temperature: 10°C

Complete Curing : >90% cured after 7 days @ 25°C

Film Thickness : 30-40 microns (by dipping)

Thinner/Cleaner : White Spirit

Mixing Ratio : 6:1 (Zinc bulk 6 parts: Solvent 1

part) Salt Spray\* (ASTM B 117): 300 Hours (at DFT of 35-40 µm)

Temperature Range : -30 to 350°C

Salt Spray\*: Salt spray test hours is proportional to film thickness.

#### **DIRECTIONS:**

- Surface must be dry and free from oil, grease or other contamination.
- Remove weld spatter and grind all sharp edges.
- For best results, spot blast exposed areas to be primed.
- Apply several thin coats (Dipping/Brushing) for greater protection than one thick coat by dipping or brush method.

Pack Size: 10 KG

Disclaimer: All information in this document is given in good faith based on lab and service experience without warranty.



ITW India Private Limited, Plot No. 34 to 37, Phase-2, IDA, TSIIC, Pashammylaram, Sangareddy Dist. -502 307, Telangana State., India. Telephone: +91 9000031515, 9100012393. Website: www.itwchemin.com

Regd. Office: ITW India Private Limited, Level 1, Lotus Plaza, 732/1, Mehrauli Gurgaon Road, Sector-14, Gurgaon - 122 001, Haryana, India.

Tolophono: +91 124 - 4284381, Facsimile: +91 124 - 4284389, E mail: infoindia@itw.com